Page 9 of Record

We hereby certify that the above road was laid and surveyed according to our order and directions, July 12th 1847

Survey of a road in the town of Porter Sept. 25m A.D. 1847

Beginning at the % Post of the south line of Sec. 18 Town 4 North of Range 11 East; thence South on the % line of Sec. 19 one mile to the % post on the north line of Sec. 30; thence South on the % line of Sec. 30 one mile to the % post on the south Tolles line of Sec. 30; thence South on the % line of Sec. 31 fifteen Rough chains to the center of the road leading from Janesville to Madison.

The whole length of the road is two miles and fifteen chains. Variation of Needle 7 3/4° Harrison Stebbins Co. Surveyor

We do hereby certify that the above Road was laid and Surveyed according to our directions and orders Sept. 25th 1847.

Survey of a Road in the town of Porter Jan. 22nd 1848

Beginning in the East line of the town at the South East corner of Sec. 24°T.4 R. 11; thence west on the South line of said Sec. 24°T.4 R. 11; thence west on the South line of said Sec. 24°T.4 R. 12; thence west on the South line of said Sec. 22°T. 21°T. 21° South East corner of Sec. 22; thence S. 68 3/4 W. 40.28 chains to the stake near the outlet of the Rhinehart Lakes. Thence S. 62 3/4 W 14 chains to stake; thence S.45 3/4 W. 26,52 chains to 1/4 Post the east line of Sec. 28; thence west on the quarter 29 0/030 line two and 1/2 miles to center of Sec. 30; thence South on line two and ½ miles to center of Sec. 30; thence South on the center line of 30 and 31,55 chains to the center of the old Madison Road; thence N. 67 3/4° W. 18 chains to the Ball Tavern.

The whole length of the road is six miles and 41 chains. Course given according to the true Meridain Variation of needle 7 3/4°

We do hereby certify that the above road was laid and Surveyed according to our orders and directions. Jan. 22nd 1848

Page 31 of Record

Survey of a Road in the Town of Porter June 10m 1850

Beginning at the West end of Van Pattens Bridge on Section 10 Town 4, North of Range 11 East at a point from which a Burr Oak 22 inches diameter; bearsN. 56½ W. 1.31 chains; thence N. 85° W. 20,22 chains to a point on the N. and S. Center line of said Section 10; thence N. 85° W. 58.28 chains to Burr Oak tree 6 inches in diamiter markeg "H";

thence S. 8312° W. 61.59 chains to west line of Section 9. Burr oak 20 inches in diamiter bears S. 70° W. 1.23 chains, thence N. 78%° W. 11.12 chains to stake; thence N. 86% W. 65.58 chains to stake on the West line of Section 8,0 being the center of the Road running Southeasterly from Cook Town to Janesville. The whole length of the Road is 2 miles fifty seven chains and nine links. Course given according to the true Meridian, Variation of needle 7 3/4°.

-3-