

paper weight-110# (minimum)

black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 4 N. R. 14 E. 4th P.M.

REV 10/23/2004

USMONREC.DWG

CORNER CODE INDEX

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	
A																									A
B																									B
C	6					5					4				3		2						1		C
D																									D
E																									E
F																									F
G	7					8					9				10		11						12		G
H																									H
J																									J
K	18					17					16				15		14						13		K
L																									L
M																									M
N																									N
O																									O
P	19					20					21				22		23						24		P
Q																									Q
R																									R
S																									S
T	30					29					28				27		26						25		T
U																									U
V																									V
W																									W
X	31					32					33				34		35						36		X
Y																									Y
Z																									Z

LIMA TWP
ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
PLACE MONUMENT SYMBOL AT PROPER
LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____

OR OBSERVATION SHEET _____

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982

CORNER CODE C-17(1)

LI518 W 1/4 COR SEC 2

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1836 BURNHAM T4N R14E NORTH BETWEEN SECTION 2 & 3
1062.60 BUR OAK 18" DIAM
2640.00 SET 1/4 SEC POST BUR OAK 10" S81E 30.36';
YELLOW OAK 16" N68W 15.18'
2904.00 WET PRAIRIE
4884.00 LEAVE PRAIRIE
5105.76 BUR OAK 12" IN DIA
5643.00 INT NORTH BOUNDARY 16.5' EAST. SET POST COR
TO 2 & 3 BUR OAK 12" S42 1/2W 109.56'; BUR
OAK 12" S12E 825'

NEXT PAGE - SUNDAY 21, JUNE 1836

1870 RUGER VOL 2 PG 22 ESTABLISHED CORNER FROM BEARING
TREE. SET STAKE. USED TO SUBDIVIDE SEC 3.

1977 BARNES VOL 5 PG 262 DUG & FOUND NOTHING SET W 1/4
COR MIDWAY BETWEEN FENCE INTERSECTION AND POSITION
OF COR IF COR WAS DECLARED LOST. REFERENCED SAME.
COR IS 2.8 WEST IF N/S FENCE & 0.4' SOUTH OF E/W FENCE.
[2.8' EAST OF DECLARED POSITION 0.1' NORTH OF DECLARED
POSITION]. SET ALUM. MON. @ FENCE INTERSECTION IS
FENCE POST IN 2.5' RADIUS CONCRETE

1977 BARNES VOL 5 PG 259 5665.76 FROM SW TO NW COR SEC 2
(ERRONEOUS G-1) 2651.9X TO SW COR SEC 2.

1977 BARNES TWP MAP W 1/4 COR (ERRONEOUS ALUM) TO SW COR
SEC 2 2651.9X; W 1/4 COR (ERRONEOUS ALUM) TO
ERRONEOUS CI. @ NW COR SEC 2 IS 3013.9X., SW 2 (ALUM)
TO W 1/4 COR SEC 2 (POLY) IS NO-37-54E 2655.30; & W 1/4
COR SEC 2 (POLY) TO NW COR SEC 2 IS NO-37-54E 3020.41.

1977 BLOMQUEST GSM VOL 6 PG 255 FD ALUM. MON. S88-01-05E
5295.11 TO SET PIPE @ E 1/4 COR SEC 2. ANGLE 91-58-55
@ E 1/4 COR SEC 2 FROM SE COR SEC 2 TO W 1/4 COR SEC 2

1983 BARNES C-17 THERE IS A DISCREPANY BETWEEN THE
CORNER SET AND THE ONE SET IN 1977. THIS IS THE
RESULT OF THE NW COR OF SEC 2 BEING CHANGED. SW COR
SEC 2 TO W 1/4 COR SEC 2 NO-37-54E 2655.30 & NO-37-54E
3020.41 TO NW COR SEC 2. REFERENCED SAME. BROKE
TOP OF ERRONEOUS W 1/4 COR SEC 2 & SET POLY MON.
4.06' FROM ALUM TO POLY MON. POLY IS 3' NORTH OF E/W
FENCE & ON LINE WITH N/S FENCE. CALLS FOR N/S
306,703.31; 2,317,461.75 AT BROKE OFF ALUM. &
306,706.93; 2,317,463.60 [SOUTH ZONE] FOR POLY.

2001 LANGONE GSM VOL 24 PG 39 FD POLY MON S88-15-27E
5294.46 TO ALUM @ E 1/4 COR SEC 2, 2649.00 TO
INTERSECTION OF 1/4 LINES. USED ERRONEOUS G-1 NEAR N
1/4 COR SEC 2. ALUM MON @ S 1/4 COR SEC 2 TO G-1 IS
NO-07-49E 5665.28. 3009.04 FROM G-1 TO INT. OF N/S
LINE. ANGLE 92-02-01 @ ALUM E 1/4 COR SEC 2 FROM SE
COR SEC 2 TO POLY @ W 1/4 COR SEC 2. ANGLE 92-02-01 @
E 1/4 COR SEC 2 FROM SE 2 (ALUM) TO POLY @ W 1/4 COR
SEC 2, ANGLE 91-25-57 @ ALUM S 1/4 COR SEC 2 FROM G-1
NEAR N 1/4 COR SEC 2 TO ALUM @ SE COR SEC 2.

2002 COMBS #14499 CI MON S88-55-20E 5295.55 TO ALUM @ E
1/4 COR SEC 2.

1/24/2012
SEAL
E100000

Donald Barnes

SHEET 1 OF 2

CORNER CODE C-17(1)

LI518 W 1/4 COR SEC 2

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED POLY MON AS SET BY ME IN C-17. THIS IS IN HARMONY WITH FENCE INTERSECTION

D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.

THE POSITION OF THE POLY MON. AS DESCRIBED BY ME IN C-17 IS CORRECT, HOWEVER AN OBSERVATION TO THIS CORNER IN THE LAST COUNTY ADJUSTMENT CONTAINES AN ENTRY BLUNDER. THE WEB COORDINATES FOR THE POLY AND ALUM MONUMENTS ARE IN ERROR.

NEW ADJUSTMENT

POINT	EASTING	NORTHING	SD	EAST	SD	NRTH	T	SD	MAJ	SD	MIN
518LI	548582.201	324795.731	0.05	0.08	7	0.09	0.06				
1518LI	548580.313	324792.139	0.06	0.07	7	0.08	0.06				

COORDINATES ON WEB SITE

POINT	EASTING	NORTHING	SD	EAST	SD	NRTH	T	SD	MAJ	SD	MIN
518LI	548578.915	324797.429	0.10	0.08	80	0.10	0.08				
1518LI	548577.022	324793.838	0.10	0.07	83	0.10	0.07				

(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

YES, IN 1983

I, **Donald Barnes**, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Donald Barnes
5180000

SHEET 2 OF 2

JAN 24, 2012

CORNER CODE C-17(1)

A.E. 7.08 REQUIREMENT