

paper weight-110# (minimum)

black nonfading ink required

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners In:
T. 4 N. R. 14 E. 4th P.M.

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
REV 10/23/2004 USMONREC.DWG

CORNER CODE INDEX

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
A																									
B																									
C																									
D																									
E																									
F																									
G																									
H																									
J																									
K																									
L																									
M																									
N																									
O																									
P																									
Q																									
R																									
S																									
T																									
U																									
V																									
W																									
X																									
Y																									
Z																									

LMA TWP

ROCK COUNTY WI

IF AVAILABLE
ROCK COUNTY COORDINATES PREFERRED

North _____ Elev. _____

East _____

Hor. Datum _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT. _____

LONGITUDE _____

NAD83(91) _____ NETWORK ADJ. YR 2010

GPS (X) _____ TRAVERSE (X) X

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a) BEARINGS ARE BASED ON: ROCK COUNTY PROJECTION

FIELD BOOK _____ PAGE # _____
OR OBSERVATION SHEET _____

SHEET 1 OF 3

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982


CORNER CODE A-19(1)

LI510 N 1/4 COR SEC 2 T4N R14E

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1835 MULLETT DEC. SOUTH BOUNDARY 5N R14E VAR 5-30E
WEST SOUTH SIDE SECTION 35
- 1056 ENTER MARSH @ NORTH
2310.00 LEAVE MARSH @ N.N.E
2640.00 SET QUARTER SECTION POST BUR OAK 10" N28E
53.46'; BUR OAK 14" N73E 29.7'
3927 ENTER MARSH @ S.W.
5082.00 LEAVE MARSH @ S.W.
5280.00 SET POST CORNER SECTIONS 34 & 35 BUR OAK
10" N51 1/2E 52.14'; BUR OAK 14" N9W 41.58'
LAND SAME
- 1977 BARNES VOL 5 PG 252 DUG & FD NOTHING. FD CUT
LIMESTONE @ S 1/4 COR SEC 35 T5N R14E. SET G-1 MON @
N 1/4 COR SEC 2. 1.05' WEST OF L.S. REFERENCED SAME.
9' SOUTH OF SOUTH PVMT EDGE.
- 1977 BARNES VOL 5 PG 259 2630.88 TO NW COR SEC 2 & NE COR
SEC 2. ON LINE WITH NW COR SEC 2 & S 1/4 COR SEC 35.
- 1982 WOLLIN A-19 RESURVEY OF KOSHONONG TOWNSHIP, BY
MILO C. JONES, AUGUST-DECEMBER, 1886. FIELD NOTES
SAY THAT BEARING TREE EVIDENCE WAS FOUND. FROM THIS
EVIDENCE A LIMESTONE MONUMENT, APPROX. 6" BY 36"
LONG WITH A SQUARED FINISHED TOP, WAS SET FOR THE
CORNER. NOTES RECORDED IN REGISTER OF DEED,
MISCELLANEOUS VOLUME 1 PAGES 389-412
- 1982 WOLLIN A-19 IN 1972 THE STONE WAS FOUND, ABOUT EVEN
WITH GROUND SURFACE ON THE EAST EMBANKMENT OF THE
ROAD. A STEEL POST & SIGN WAS SET NEXT TO THE STONE.
1977 ROCK COUNTY SURVEYOR, ESTABLISHED THE CORNER
FOR N1/4 COR SEC 2 1.05' WEST OF THE CORNER STONE TO
S 1/4 COR SEC 35. CORNER WAS SET EQUAL DISTANCE
BETWEEN SECTION CORNERS OF SECTION 2. AN ALUM. WAS
SET FOR THE CORNER.
- 1982 WOLLIN A-19 REFERENCED ALUM & SHOWS CUT L.S. ALUM
IS 1.05 WEST OF L.S.
- 1982 WOLLIN #05983 TIE SHEET. SAME AS A-19
- 1983 BARNES VOL 6 PG 308 THE N 1/4 COR OF SEC 2 WAS SET BY
USING THE NW COR OF SEC 2 PRIOR TO THE FINDING OF THE
CUT LIMESTONE. USING THE CUT LIMESTONE WILL
DRASTICALLY MOVE THE BEFORE MENTIONED CORNERS.
TOM WOLLEN, JEFFERSON COUNTY SURVEYOR, WILL DIG
FOR THE S 1/4 COR OF SEC 36 T5N R14E. ONCE HE DOES
THAT, I WILL RESET THE N /4 AND THE NE CORNER OF SEC 2.
- 2000 LANGONE CSM VOL 24 PG 39 FD ALUM MNT. SO-07-49W
5665.28 TO ALUM @ S 1/4 COR SEC 2, 3009.04 TO
INTERSECTION OF 1/4 LINES.

THIS RECORD IS CREATED TO CLEARLY EXPLAIN THE
REESTABLISHMENT AND HISTORY OF THE N 1/4 COR SEC 2.

SEAL 
Emboss

SHEET 1 OF 3

1/24/2012

CORNER CODE A-19(1)

LI510 N 1/4 COR SEC 2 T4N R14E

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

- 1835 MULLETT DEC. SOUTH BOUNDARY 5N R14E VAR 5-30E
WEST SOUTH SIDE SECTION 35
- 1056 ENTER MARSH @ NORTH
2310.00 LEAVE MARSH @ N.N.E
2640.00 SET QUARTER SECTION POST BUR OAK 10" N28E
53.46'; BUR OAK 14" N73E 29.7'
3927 ENTER MARSH @ S.W.
5082.00 LEAVE MARSH @ S.W.
5280.00 SET POST CORNER SECTIONS 34 & 35 BUR OAK
10" N51 1/2E 52.14'; BUR OAK 14" N9W 41.58'
LAND SAME
- 1977 BARNES VOL 5 PG 252 DUG & FD NOTHING. FD CUT
LIMESTONE @ S 1/4 COR SEC 35 T5N R14E. SET G-1 MON @
N 1/4 COR SEC 2. 1.05' WEST OF L.S. REFERENCED SAME.
9' SOUTH OF SOUTH PVMT EDGE.
- 1977 BARNES VOL 5 PG 259 2630.88 TO NW COR SEC 2 & NE COR
SEC 2. ON LINE WITH NW COR SEC 2 & S 1/4 COR SEC 35.
- 1982 WOLLIN A-19 RESURVEY OF KOSHONONG TOWNSHIP, BY
MILO C. JONES, AUGUST-DECEMBER, 1886. FIELD NOTES
SAY THAT BEARING TREE EVIDENCE WAS FOUND. FROM THIS
EVIDENCE A LIMESTONE MONUMENT, APPROX. 6" BY 36"
LONG WITH A SQUARED FINISHED TOP, WAS SET FOR THE
CORNER. NOTES RECORDED IN REGISTER OF DEED,
MISCELLANEOUS VOLUME 1 PAGES 389-412
- 1982 WOLLIN A-19 IN 1972 THE STONE WAS FOUND, ABOUT EVEN
WITH GROUND SURFACE ON THE EAST EMBANKMENT OF THE
ROAD. A STEEL POST & SIGN WAS SET NEXT TO THE STONE.
1977 ROCK COUNTY SURVEYOR, ESTABLISHED THE CORNER
FOR N1/4 COR SEC 2 1.05' WEST OF THE CORNER STONE TO
S 1/4 COR SEC 35. CORNER WAS SET EQUAL DISTANCE
BETWEEN SECTION CORNERS OF SECTION 2. AN ALUM. WAS
SET FOR THE CORNER.
- 1982 WOLLIN A-19 REFERENCED ALUM & SHOWS CUT L.S. ALUM
IS 1.05 WEST OF L.S.
- 1982 WOLLIN #05983 TIE SHEET. SAME AS A-19
- 1983 BARNES VOL 6 PG 308 THE N 1/4 COR OF SEC 2 WAS SET BY
USING THE NW COR OF SEC 2 PRIOR TO THE FINDING OF THE
CUT LIMESTONE. USING THE CUT LIMESTONE WILL
DRASTICALLY MOVE THE BEFORE MENTIONED CORNERS.
TOM WOLLEN, JEFFERSON COUNTY SURVEYOR, WILL DIG
FOR THE S 1/4 COR OF SEC 36 T5N R14E. ONCE HE DOES
THAT, I WILL RESET THE N /4 AND THE NE CORNER OF SEC 2.
- 2000 LANGONE CSM VOL 24 PG 39 FD ALUM MNT. SO-07-49W
5665.28 TO ALUM @ S 1/4 COR SEC 2, 3009.04 TO
INTERSECTION OF 1/4 LINES.

THIS RECORD IS CREATED TO CLEARLY EXPLAIN THE
REESTABLISHMENT AND HISTORY OF THE N 1/4 COR SEC 2.

Donald Barnes
SE

Embloss

1/24/2012

SHEET 1 OF 3

CORNER CODE A-19(1)

