U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T.4_N., R. /4_E

CORNER CODE INDEX

| UMA | | TWI |
|-----|--------|-----|
| | COUNTY | WI |

IF AVAILABLE ROCK COUNTY COORDINATES PERFERRED

North ______ Elev. _____

East _____ Vert. Datum _____

LATITUDE _____ ELLIPS. HT.

LONGITUTE _____ ERVERSE (X) ___

BASED ON THE FOLLOWING CONTROL:

| | ◆ CORNER N | |
|--|------------|--|
|--|------------|--|

LOCATION ON ABOVE INDEX

WITNESS MONUMENT

BEARINGS ARE BASED ON:

(a)

| | SHEET OF | | | |
|---|-----------------|--|--|--|
| FIELD BOOKPAGE # | SHEETOF | | | |
| SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT | AND SURROUNDING | | | |
| PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH. | | | | |
| PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982 | | | | |

LI526

(B)Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

BARNES VOL 6 PG 249 FOUND 1" IRON PIPE IN MON. BOX. REFERENCE: VOL 4, PAGE 445, FIELD BOOK LIMA, PAGE 43

1982 BARNES E-13 SET POYSTYRENE MON.

FOUND POLY. MON. & 3 REFERENCE MONUMENTS.

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED FOUND PERPETUATED LOCATION.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Under Faires
May 28, 1999

Number of included sheets 1

CORNER CODE E-11(1)

