

# U.S. PUBLIC LAND SURVEY MONUMENT RECORD

For Public Land Survey Corners in:

WI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT

T. 3N., R. 13E

### CORNER CODE INDEX

A	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
B	6					9					12				15						18				
C																									
D																									
E																									
F																									
G	1					8						10									11			12	
H																									
J																									
K																									
L	18					17						16									14			13	
M																									
N																									
O																									
P	19					20						21									23			24	
Q																									
R																									
S																									
T	30					29						28									26			25	
U																									
V																									
W																									
X	31					32						33									35			36	
Y																									
Z																									

HARMONY TWP  
ROCK COUNTY WI

IF AVAILABLE  
ROCK COUNTY COORDINATES PREFERRED

North \_\_\_\_\_ Elev. \_\_\_\_\_

East \_\_\_\_\_

Hor. Datum \_\_\_\_\_ Vert. Datum \_\_\_\_\_

LATITUDE \_\_\_\_\_ ELLIPS. HT. \_\_\_\_\_

LONGITUDE \_\_\_\_\_

GPS (X) \_\_\_\_\_ TRAVERSE (X) \_\_\_\_\_

BASED ON THE FOLLOWING CONTROL:

PLACE MONUMENT SYMBOL  AT PROPER LOCATION ON ABOVE INDEX

CORNER MONUMENT

WITNESS MONUMENT

(a)

BEARINGS ARE BASED ON:

FIELD BOOK \_\_\_\_\_ PAGE # \_\_\_\_\_

SHEET 1 OF 2

SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.

PLANNING & ZONING COMMITTEE ADOPTED THE ABOVE FORM ON 12/2/1982

CORNER CODE X-25(1)

HA620

*(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.*

- 1860 RUGER VOL 1 PG 135 SET LIMESTONE 10X4X4 SURROUNDED WITH 3 LIMESTONES. 2638.68' TO SE COR SEC 36.
- 1867 LOCKE VOL 1 PG 300 FOUND OLD STAKE & IRON WOOD STAKE WITH HH ON E/W & 2 LIMESTONES ON NORTH, & 2 ON SOUTH IN CENTER OF HIGHWAY. 2560.96 VAR 4-48 TO CENTER SEC 31 & 5200.96 TO E ¼ COR SEC 31 JOHNSTOWN TWP.
- 1870 RUGER REMONUMENTATION FIELD NOTES PG 223 & 224. NORTH ON EAST LINE OF S.E. ¼ SEC 36 ON A VAR 7-03 AT 2640.44' INTERSECTED ¼ LINE 2.31' WEST OF QUARTER COR. FOUND STAKE SURROUNDED BY STONES ON COR. SET BY SELF. NORTH ON EAST LINE OF N.E. ¼ SEC 36 ON A VAR 7-20 AT 2636.70' INTERSECTED NORTH BOUNDARY LINE AT COR. FOUND STAKE SURROUNDED BY STONES ON COR. SET BY SELF.
- 1971 LEE VOL 4 PG 547 DUG & FOUND CUT STONE MON. REFERENCED SAME.
- 1981 BARNES VOL 6 PG 175 FOUND RECORD STONE. SET ALUM. MON. FOUND REFERENCE MONUMENTS.
- 1984 BARNES X-25 SEE JOHNSTOWN FILES.

FOUND ALUM. MON. 0.15' DEEP. 1' NORTH AND 1' WEST OF CENTER OF PAVEMENT. FOUND REFERENCE MONUMENTS. MONUMENT WILL BE GROUND OUT AND ROAD REPAVED.

*C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?*

ACCEPTED FOUND MONUMENT.

*D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.*

*(E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.*

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal

*Donald Barnes*

emboss

OCT 25, 2000

Number of included sheets **1**

CORNER CODE **X-25(1)**

A-E 7.08 REQUIREMENT

