U.S.

ROCK COUNTY PROJECTION

BEARINGS ARE BASED ON:___

PUBLIC LAND SURVEY MONUMENT RECORD

FUI			Survey (R./O				VI ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT REV 10/23/2004 USMONREC.DWG
1 2		COI	RNER C	ODE IN	DEX	22 23 24 25	MAGNOLIA TWP
A 1 2 B C D	6	6	>	3	7		ROCK COUNTY WI C IF AVAILABLE
F G	1	8	9	10	V	P	E ROCK COUNTY COORDINATES PERFERRED F G
H J K	19		16	15	A		H North Elev J K East
M N O			Y	Y			M N Hor. Datum Vert. Datum
P Q R	79	20		27	3		P LATITUDE ELLIPS. HT
S T U	30	29	28	2	70		S LONGITUDE
V W X Y	3	37	3	20	35	30	W
	LACE	MONUMEN	9 10 11 12 1 T SYMBOL BOVE INDE	◆ AT P		1 22 23 24 25	z BASED ON THE FOLLOWING CONTROL:
(a)			CORNER		MENT	WITNESS MONUMENT	
] 						

FIELD BOOK PAGE #	/ 7
OR OBSERVATION SHEET	SHEETOF Z
SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONU	MENT AND SURROUNDING
PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA ANI	D DEPTH.
PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/198	
CO	RNER CODE $G/()$

MA534 W 1/4 COR SEC 7

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETTE (SEP 11TH) NORTH EAST SIDE SEC 13

2640.00 SET 1/4 SECTION POST BUR OAK 16 S30W 30.36', BUR OAK 15 N49W 63.36'

5280.00 SET POST CORNER SECTIONS 12 & 13 BUR OAK 14 S13W 108.9', BUR OAK 18 N2OW 36.96'

1833 HARRISON (DEC 7TH) START DEC 1ST FINISHED DEC 7TH

WEST BET SECS 6 & 7

1947.0 SPRING BROOK 5.28 CRS SOUTH

2046 CREEK 33' CRS N.W.

2640.0 QUARTER SEC COR {BUR O 12 SBW 198'? NO OTHER NEAR BURR O 12} MARKED

3432 ENTER SCATTERING TIMBER IN CREEK BOTTOM

5335.44 INT. W BDY. SET COR TO 6 & 7 {BURR O 18 N46E 205.26'

LAND LEVEL & WET 3RD RATE TIMBER BURR O.

WEST BET. SECS 7 & 18

1184.7 BURR 0 12 IN DIAM.

2640.00 QUARTER SEC COR {RED 0 10 N35W 22.44', W.O. 10 S67W 17.82'} RED 0 16, WO 10} MARKED

5344.68 INT W. BOUNDARY {BURR OAK 18 N51E178.2' & BURR OAK 12 S75E 221.1'.

1833 HARRISON (DEC 8TH) TWP START DEC 8TH FINISHED FEB 8TH EAST ON RAND BET 12 & 13

1881 LEAVE MARSH

2640 TEMPY 1/4 SEC. COR

2937.0 SPRING BROOK 5.28 CRS N 2 & 3 CH S OF LIME ?? ?? SPRING

5227.0 INT. E BDY 198 N OF P

LAND GENERALLY LEVEL 3 RD RATE AND WET WITH TIMBER OF RED & BURR OAK.

EAST ON RAN BET 13 & 24 T3N R9E

2640.0 TEMPY 1/4 SEC COR.

5226.54 INT. E BDY 124.08 N OF POST LAND LEVEL 2ND RATE TIMBER WHITE OAK & BURR & UNDERGROWTH GRASS & WEEDS

- 1855 CHURCH VOL 1 PG 53 5320.92 TO E 1/4 COR SEC 7, 2610.96 TO NW COR SEC 7, & 2610.96 TO SE COR SEC 7.
- 1937 SUNNY VOL 3 PG 353 THIS CORNER IS NOT IN BLACKTOP. 2621.4 TO SW COR SEC 7.
- 1966 BATTERMAN VOL 4 PG 282 SHOWS TIES BUT STATES NOTHING ABOUT CORNER. ON LINE WITH E/W FENCE ON THE WEST SIDE OF RD REFERENCED CORNER.
- 1995 BARNES VOL 6 PG 443 SO-19-11E 2624.40 TO SW COR SEC 7
- 1995 BARNES L11 SE COR SEC 13 T3N R9E TALARCZYK SET ALUM BY PROPORTIONATE MEASUREMENT & EXISTING PHYSICAL EVIDENCE. HE REFERENCED SAME & CALLS FOR MON @ CENTER OF PVMT. I DID NOT ACCEPT FO ALUM. MON. BECAUSE I ESTABLISHED THE SE COR OF SEC 13 IN A DIFFERENT LOCATION THAN TALARCZYK. THE NEW LOCATION WILL AFFECT THE LOCATION OF THE E 1/4 COR SEC 13 SINCE TALARCZYK USED PROPORTIONATE MEASUREMTN. I DID NOT DIG FOR OR ESTABLISH THE E 1/4 COR SEC 13. THE ALUM

емаравер

SHEET 1 OF 2

CORNER CODE G-1(1)

Den Barres 2-11-2011 MA534 W 1/4 COR SEC 7

MON TALARCZYK SET @ THE E 1/4 COR SEC 13 COORDINATES ARE 287,953.92; 400,407.88

1995 BARNES G-1 FOUND PK THAT IS IN HARMONY WITH 2 REFERENCE PIPES. PK IS 1.5' WEST OF CENTER OF PVMT. & 2' NORTH OF E/W CENTER OF PVMT. 2624.40 TO NW CORNER OF SEC 18. S8-44-22E 444.05 TO GPS MON ALBANY GPS [269,073.789; 2,138,223.049]

BETWEEN SEC 35 & 36 T1N R9E THE DISTANCE BETWEEN THE RANDOM STATE LINE & THE CURRENT STATE LINE IS 3993', BETWEEN SEC 33 & 34 IT IS 3828', BETWEEN 32 & 33 IT IS 3927', BETWEEN 31 & 32 IT IS 3432' BETWEEN SEC 31 & 32 T1N R12E IT IS 5049'

- C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

 ACCEPTED FOUND PK.
- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

NO

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Embossed

2-11-2011

Seal

SHEET 2 OF 2
CORNER CODE G-1(1)

EMBOSS LAND SURVEYOR SEAL