U.S.

BEARINGS ARE BASED ON:____

PUBLIC LAND SURVEY MONUMENT RECORD

For	Public	Land	Survey 9	corners	In:	Wi	ADMINISTRATIVE CODE A-E 7.08 REQUIREMENT
	T	. <u>Z</u> n	. R. #	∑_E. ∠	th P.M.		REV 10/23/2004 USMONREC.DWG
		CC	RNER C	ODE INI	DEX		11 1 C 1 C 1 C TWVD
A 1 2	3 4 5	6 7 8	9 10 11 12 1	3 14 15 16 1	7 18 19 20 21	22 23 24 25 _A	MAGNOUA TWP
В —		5		2	1	B	ROCK COUNTY WI
C	6	7		7		C	IF AVAILABLE
E						E	ROCK COUNTY COORDINATES PERFERRED
F G		4	1	10		F G	
H -						H H	North Elev.
Ј К	4		1,6	4	. >	J K	East
L M	10	*				L	
N _						N	Hor. Datum Vert. Datum
O P	19	0		3		OP	
Q	Y					Q	LATITUDE ELLIPS. HT
R						R	LONGITUDE
т	30	29	1 25	12 -	76	T	LONGITUDE
U V						U	NAD83(91) NETWORK ADJ. YR 2010
w		2			25	y o w	V
X Y	2	17	7	ר' ד	7	7 X	
$z \bigsqcup_{i=1}^{n}$	2 3 4 5	6 7 8	9 10 11 12 1	3 14 15 16	17 18 19 20 21	22 23 24 25	BASED ON THE FOLLOWING CONTROL:
. 1	PLACE M	ONUME	NT SYMBOL BOVE INDE	AT P	ROPER		
					MENT	0 '	WITNESS MONUMENT
(a)		T	COMILIC	17101101	VILLITIE	O	
	1						
	ĺ						
Z	l l						
ROJECTION	İ						
C	1						
CO	1						
	1						
TY	1						
5							
S	1						
ROCK COUNTY P	İ						
RC							

FIELD BOOK PAGE #								
OR OBSERVATION SHEET	SHEET OF							
SHOW A PLAN VIEW DRAWING DEPICTING THE CORNER MONUMENT AND SURROUNDING								
PHYSICAL FEATURES, INCLUDING THE EXCAVATION AREA AND DEPTH.	1							
PLANNING & ZONING COMMITTEE ADOPTED THIS FORM ON 12/2/1982	- cha							
CORNER	CODE <u> </u>							

NWSEC7 MA521

(B) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

1833 MULLETTE (SEP 11TH) NORTH ON EAST SIDE SEC 24

> 1233.54 BUR OAK 16

SET 1/4 SEC POST BUR OAK 10 N31 1/2W 2640.0 21.78, BUR OAK 16 S20W 26.4 BUR OAK 16

5280.00 SET POST CORNER SECTIONS 13 & 24 W. OAK 12 S73W 201.96', BLACK OAK 4 N40W 67.32' NORTH EAST SIDE SEC 13

SET 1/4 SECTION POST BUR OAK 16 S30W 2640.00 30.36', BUR OAK 15 N49W 63.36'

5280.00 SET POST CORNER SECTIONS 12 & 13 BUR OAK 14 513W 108.9', BUR OAK 18 N2OW 36.96

1833 HARRISON (DEC 7TH) START DEC 1ST FINISHED DEC 7TH WEST BET SECS 6 & 7

> SPRING BROOK 5.28' CRS SOUTH 1947.0

CREEK 33' CRS N.W. 2046

2640.0 QUARTER SEC COR (BUR O 12 SBW 198'? NO OTHER NEAR BURR O 12 MARKED

3432 ENTER SCATTERING TIMBER IN CREEK BOTTOM

INT. W BDY. SET COR TO 6 & 7 (BURR O 18 5335.44 N46E 205.26

> LAND LEVEL & WET 3RD RATE TIMBER BURR O. WEST BET. SECS 7 & 18

1184.7 BURR O 12 IN DIAM.

QUARTER SEC COR {RED 0 10 N35W 22.44', 2640.00 W.D. 10 S67W 17.82' RED 0 16, WO 10 MARKED

INT W. BOUNDARY (BURR OAK 18 N51E178.2' & 5344.68 BURR OAK 12 S75E 221.1'.

1833 HARRISON (DEC 8TH) TWP START DEC 8TH FINISHED FEB 8TH EAST ON RAND BET 12 & 13

> LEAVE MARSH 1881

2640 TEMPY 1/4 SEC. COR

SPRING BROOK 5.28' CRS N 2 & 3 CH S OF 2937.0 ?? SPRING LIME ??

INT. E BDY 198 N OF P 5227.0

LAND GENERALLY LEVEL 3 RD RATE AND WET WITH TIMBER OF RED & BURR OAK.

EAST ON RAN BET 13 & 24 T3N R9E

TEMPY 1/4 SEC COR. 2640.0

INT. E BDY 124.08' N OF POST LAND LEVEL 5226.54 **2ND RATE**

> TIMBER WHITE DAK & BURR & UNDERGROWTH **GRASS & WEEDS**

- 1855 CHURCH VOL 1 PG 53 STATES NOTHING ABOUT MON. VAR S81-1/2E 2680.92 TO N 1/4 COR SEC 7, 2610.96 TO W 1/4 COR SEC 7 & 5221.92 TO SW COR SEC 7
- 1864 LOCKE VOL 1 PG 205 FD B.T. & STAKE VAR8-15 2671.02 TO N 1/4 COR SEC 7 [FD REMAINS OF B. TREES] & VAR7-55 2701.05 TO W 1/4 COR SEC 6 [SET LIMESTONE 24X15X6]. FROM SW 6 TO NW SEC 6 VAR 7-55 4886.64'. NE COR SEC 12 T3NR9E IS 924' SOUTH OF NW COR SEC 6. NE COR SEC 12 IS 35.31 NORTH OF W 1/16TH COR OF NW 1/4 OF SEC 6 (SET BR. O. STAKE]
- 1937 SUNNY VOL 3 PG 353 THIS COR IS NOT IN BLACKTOP. 2621.4 TO SW COR SEC 7 (FD HH SET BY RUGER SET 1 1/2 X 10 PIPE WITH CAP ON TOP FLUSH WITH BLACKTOP PAVEMENT.
- FD HH 18X10 & REFERENCED 1966 BATTERMAN VOL 4 PG 282 SAME. SHOWS ON LINE WITH E/W FENCE ON EAST SIDE OF RD.

SHEET 1 OF 2 CORNER CODE E-1

EIEAL Daves 2-11-261)

MA521

- 1978 BARNES VOL 5 PG 459 SET ALUM MON. 1367.63 TO E 1/4 COR SEC 12 T3N R9E . COR IS 1352 SOUTH OF E/W FENCE ON ROCK COUNTY SIDE. @ W 1/16TH COR OF SW 1/4 OF SEC 6 DUG 4X15 HOLE 8' DEEP & FOUND NOTHING. NE COR SEC12 T3N R9E IS 929.18 SOUTH OF NW COR SEC 6. NW COR SEC 7 IS 1367.63 SOUTH OF FD ALUM MON SET BY TALARCZYK AS THE E 1/4 COR SEC 12. ANGLE AT ALUM FROM W 1/4 COR SEC 6 TO SW COR SEC 6 IS 179-54-19
- 1978 BARNES VOL 5 PG 460 SET ALUM MON FROM TIES. IT IS EAST OF CENTER OF PVMT. COR IS ON LINE WITH E/W FENCE REFERENCED COR.
- 2009 SAUSER #16158 COUNTY COORDINATES N 291841.53; E. 400,380.74 FD TIES NOT MON AT COR.

BETWEEN SEC 35 & 36 T1N R9E THE DISTANCE BETWEEN THE RANDOM STATE LINE & THE CURRENT STATE LINE IS 3993', BETWEEN SEC 33 & 34 IT IS 3828', BETWEEN 32 & 33 IT IS 3927', BETWEEN 31 & 32 IT IS 3432'

BETWEEN SEC 31 & 32 T1N R12E IT IS 5049

C) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

ACCEPTED ALUM. MON.

- D) Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (a), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 4 of the witness monuments shown on the drawing in (a), above.
- (E) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning the corner location.

I, Donald Barnes, hereby certify that the corner location as identified by the corner code index was determined by me under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

seal panes

Embossed

2-11-2011

SHEET 2 OF 2

CORNER CODE E-1

A-E 7.08 REQUIREMENT